



## CPC Molding Oil AR60

- CPC Molding Oil AR60 is mainly used as wooden or metallic molds-separating and rust-preventive oil to prevent from adhesion between molds and castings, and to keep surfaces clean.
- With functions of anti-rust and water metathesis, the oil can be used in rust -preventive operation for mechanical parts indoors.
- Due to solvent included, please be careful to store and apply the oil. Don't heat or keep away from fire to ensure safety.
- Always tighten the container when not in use. A suitable amount of solvent can be added into the oil and stirred properly if solvent is over volatile.
- Packages: (1) 200 liter drum  
(2) 19 liter pail
- The typical data are listed as follow:

Sp. Gr., 15.6°C/15.6°C, D4052	0.8626
Viscosity, Kin., cSt @40°C, D445	7.89
@100°C, D445	2.30
Viscosity Index, D2270	105
Pour Point, °C, D6749	-12
Flash Point, PMCC, °C,D93	62
Color, D1500	4.0
Acid Number, mg KOH/g, D664	0.24
Rust-Preventive, D665-A	Pass
Ash, wt%, D482	0.365
Product No.	LA72943

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.