



CPC Way Lubricant

- CPC Machine Way Lubricant is especially refined and added special additives with excellent metal surface adhesion that can lubricate folding-face and bed-stage way of various heavy duty machine to avoid or reduce bed-stage stick-slip and promote the quality of processed products.
- The oils meet the machine way specifications of American Cincinnati Milacron P-47 and become the one of the company approved products.
- Packages: (1) 200 liter drum
(2) 19 liter pail (for 68)
- The typical data are listed as follow:

Grade No.	32	68
Sp. Gr., 15.6°C/15.6°C, D4052	0.8723	0.8855
Viscosity, Kin., cSt @ 40°C, D445	33.3	68.4
@100°C, D445	5.57	8.82
Viscosity Index, D2270	104	101
Pour Point, °C, D6749	-12	-12
Flash Point, COC, °C, D92	236	236
Color, D1500	1.5	3.0
Acid Number, mg KOH/g, D664	1.29	1.27
ISO VG Grade	32	68
Product No.	LA81032	LA81068

Grade No.	150	220
Sp. Gr., 15.6°C/15.6°C, D4052	0.8922	0.8961
Viscosity, Kin., cSt @ 40°C, D445	143.3	241.0
@100°C, D445	14.41	20.08
Viscosity Index, D2270	98	96
Pour Point, °C, D6749	-12	-12
Flash Point, COC, °C, D92	240	284
Color, D1500	4.5	4.5
Acid Number, mg KOH/g, D664	1.22	1.15
ISO VG Grade	150	220
Product No.	LA81150	LA81220

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.