



## CPC Process Oil (Paraffinic Base)

- CPC Process Oil (Paraffinic Base) is a high quality paraffinic base process oil and its quality is equivalent to US ASTM No.104 paraffinic base, used in processes of various natural and artificial rubbers to give softening and lubricating effects.
- Package: in bulk
- The typical data are listed as follow:

Grade No.	No.5
Sp. Gr., 15.6/15.6°C, D4052	0.8691
Viscosity, Kin., cSt @40°C, D445	23.62
@100°C, D445	4.47
Viscosity Index, D2270	97
Flash Point, COC, °C, D92	225
Pour Point, °C, D6749	-12
Color, D1500	L0.5
Sulfur, %, D4294	0.18
Acid Number, mg KOH/g, D664	0.01
Aniline Point, °C, D611	101
Volatile Matter, 162.8°C, 3hr,wt %, D972	0.28
Asphaltenes , wt%, D2007	Nil
Polar Compounds, wt%, D2007	0.28
Aromatics, wt%, D2007	29.24
Saturated Hydrocarbons, wt%, D2007	70.48
Carbon Type, wt%,D2140	
C <sub>A</sub>	3
C <sub>N</sub>	34
C <sub>P</sub>	63
Product No.	LB79005

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.