



CPC Marilube Oil W304, W404, W504

- CPC Marilube Oils are designed for the modern novel cylinder piston engines which burn high-sulfur heavy fuel oils.
- The oils obtain Wartsila company certifications and can lubricate the full range of cylinder piston engines designed by Wartsila.
- The oils possess good acid neutralizing capacity and excellent performances, such as anti-oxidation, anti-corrosion, anti-rust and anti-wear.
- The oils possess a very excellent detergent and dispersive performance to keep the cylinder inner-walls and the pistons very clean in use of heavy fuel oil condition.
- Packages: (1) in bulk
(2) 200 liter drum
- The typical data are listed as follow:

Grade No.	W304	W404	W504
SAE Viscosity No.	40	40	40
Sp. Gr., 15.6°C/15.6°C,D4052	0.9082	0.9145	0.9199
Viscosity Kin. cSt @ 40°C,D445	139.2	142.0	138.0
@ 100°C,D445	14.08	14.16	14.00
Viscosity Index, D2270	98	97	98
Pour Point, °C, D6749	-6	-6	-6
Flash Point, COC, °C,D92	302	268	240
Base Number, mg KOH/g, D2896	30.8	40.3	50.4
Product No.	LB52304	LB52404	LB52504

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.