



CPC Super Duty Marilube Oil HB-30, HB-40

- CPC Super Duty Marilube Oils are high-performance super-duty engine oils. The oils are applied to the engines of large/medium-sized fishing boats or land-based diesel engines which use class A fishing boat oils or regular diesel with about 1% sulfur content.
- The oils contain excellent detergent dispersant that can inhibit the deposits of the engine components to achieve a high level of cleanliness. They possess the excellent properties of high-temperature thermal oxidation stability, anti-wear, and anti-rust.
- The TBNs of the oils are 20 mg KOH/g around. The oils can effectively neutralize acidic sulfide after fuel combustion to reduce corrosive wear.
- Packages: (1) in bulk
(2) 200 liter drum
- The typical data are listed as follows:

Grade No.	HB-30	HB-40
SAE Viscosity No.	30	40
Sp. Gr., 15.6°C/15.6°C, D4052	0.8974	0.9008
Viscosity, Kin., cSt @40°C, D445	104.1	151.4
@100°C, D445	11.60	14.97
Viscosity Index, D2270	99	99
Pour Point °C, D6749	-6	-6
Flash Point COC°C, D92	256	266
Base Number, mg KOH/g, D2896	20.0	20.0
Product No.	LB54163	LB54164

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.