



CPC Superfleet CH4 Motor Oil

- CPC Superfleet CH4 Motor Oil is manufactured from refined paraffinic base oils and formulated with the latest additives. The oil does not only meet the specifications of API CH4 for bus/vans manufacturers in USA, Japan and other countries, but also meet the requirement of extended drain for bus/vans manufacturers in European. It contains high performance additives, such as detergents, antioxidants, anti-wear, rust and corrosion inhibitors, anti-foam, etc.
- The quality of the oil meets or exceeds the following oil specifications:
API CH4/CG4/CF4/SJ, Cummins CES 20076 and Mack EO-M Plus in USA.
ACEA E3/B3/A3, MB 228.3/229.1, Volvo VDS-2, MAN 271, and MTU Type 2 in European.
- The oil is widely used in various vehicles or engineering machinery with four-stroke diesel engines, and turbocharged and supercharged diesel engines, also used in four-stroke gasoline engines.
- The oil is a SAE 15W/40 oil and is used for all seasons
- Packages: (1) 200 liter drum
(2) 19 liter pail
(3) 4 liter bottle, 4 liter*6 case
- The typical data are listed as follow:

SAE Viscosity No.	15W/40
Sp. Gr., 15.6°C/15.6°C, D4052	0.8800
Viscosity, Kin., cSt @40°C	120.1
@100°C	15.70
Viscosity Index, D2270	138
Pour Point, °C, D6749	-21
Flash Point, COC, °C, D92	240
Fire Point, COC, °C, D92	260
Color, D1500	L4.0
Base Number, mg KOH/g, D2896	10.3
Sulfated Ash, %, D874	1.25
API Service Classification	CH4/CG4/CF4/SJ
Product No.	LB51740

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.